





ELMA

6512-54-007

ELMA WALL LAMP

Lighting features	
LED Characteristics	SMD
Number of LEDs	40 LED
Light Source Lumen	1790 lm
Item Lumen	1121 lm
Light Source Efficiency	180 lm/W @85°C
Item Efficiency	86 lm/W @85°C
Color Temperature	White 4000K
Optics	Opal
Typical CRI	85
Minimum CRI	80
SDCM	3 STEP
Photobiological Risk	RG0
Energy Efficiency Class	A

Electrical features	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	13W
Power Factor	> 0.8
Control System	On/Off
Driver	Included
Power Supply Type	Costant Current
Driver Output	350mA
Driver Input	220/240V~ 50/60Hz
Driver Protection	Mains surge 1kV; (L/N - PE) 2kV

Mechanical features	
Housing material	Aluminum frame and polycarbonate
Housing color	White
IP	IP40
IK	08
Diffuser / Protective shield	Opal polycarbonate
Operating ambient temperature	-20°C / +45°C
Storage ambient temperature	-20°C / +60°C
Item Dimensions	67x517x70mm - 1,4kg

Others	
Luminous Flux Maintenance	L80 100000h
Driver Lifespan	50000
Packaging Dimensions	1.7kg
International standard compliance	EN 60598-1; EN 60598-2-1; EN 62471 + IEC/TR 62778; EN 55015; EN 61547; EN 61000-3-2; EN 61000-3-3; EN IEC 63000
Eancode	8019282565406
Made In	Italy
Insulation Class	CL1



