Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it



TAIMA

6519-21-364

Dimmable LED lamp with on/off switch and USB-C 5VDC 2A

Lighting features	
LED Characteristics	**COB**
Number of LEDs	**1**
Light Source Lumen	**400 lm**
Item Lumen	**300 lm**
Light Source Efficiency	**133 lm/W @85°C**
Item Efficiency	**75 lm/W @85°C**
Color Temperature	**White 3000K**
Optics	**32°**
Minimum CRI	**>80**
SDCM	**5 STEP**
Photobiological Risk	**1**
Energy Efficiency Class	A↑G G

Electrical features	
Input Voltage	**100/240V AC 50/60Hz**
Total Absorbed Power	**4W**
Power Factor	**>0,9**
Control System	**Push dimmer**
Driver	**Included**
Power Supply Type	**Costant Voltage & Constant current**
Driver Output	**200mA**
Driver Input	**110-127V AC / 220-240V AC 50/60Hz**
Through-Wiring	**No**

Mechanical features	
Housing material	**Metal frame**
Housing color	**Black**
IP	**IP20**
Mounting	**With steel bracket**
Operating ambient temperature	**+0°C / +40°C**
Item Dimensions	**80x120x40mm - 0.5kg**

Others	
Packaging Dimensions	**125x125x190mm - 0.6kg**
International standard compliance	**EN60598-1; EN60598-2-1; EN 62471 + IEC TR62778; EN55015; EN 61547-1; EN61000-3-2; EN61000-3-3**
Eancode	**8019282544104**
Insulation Class	CL1

CE

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

