



TAIMA

6519-21-364

Dimmable LED lamp with on/off switch and USB-C 5VDC 2A

Lighting features	
LED Characteristics	COB
Number of LEDs	1
Light Source Lumen	400 lm
Item Lumen	300 lm
Light Source Efficiency	133 lm/W @85°C
Item Efficiency	75 lm/W @85°C
Color Temperature	White 3000K
Optics	32°
Minimum CRI	>80
SDCM	5 STEP
Photobiological Risk	1
Energy Efficiency Class	A ↑ G

Electrical features	
Input Voltage	100/240V AC 50/60Hz
Total Absorbed Power	4W
Power Factor	>0,9
Control System	Push dimmer
Driver	Included
Power Supply Type	Costant Voltage & Constant current
Driver Output	200mA
Driver Input	110-127V AC / 220-240V AC 50/60Hz
Through-Wiring	No

Mechanical features	
Housing material	Metal frame
Housing color	Black
IP	IP20
Mounting	With steel bracket
Operating ambient temperature	+0°C / +40°C
Item Dimensions	80x110x35mm - 0.47kg

Others	
International standard compliance	EN60598-1; EN60598-2-1; EN 62471 + IEC TR62778; EN55015; EN 61547-1; EN61000-3-2; EN61000-3-3
Eancode	8019282544104
Insulation Class	CL1



