




PSAR2 R DALI - 110V

6823-10-296

Red Light - Recessed fixture for living rooms



Lighting features	
LED Characteristics	SMD
Number of LEDs	30
Item Lumen	61 lm
Item Efficiency	13 lm/W @85°C
Color Temperature	Red Dominant Wavelength: >619nm <625nm
Optics	Opal
Photobiological Risk	RG0

Electrical features	
Input Voltage	110/127V AC - 220/240V AC 50/60Hz
Total Absorbed Power	5W
Power Factor	> 0,9
Control System	DALI
Driver	Included
Power Supply Type	Costant Voltage
Driver Output	24VDC
Driver Input	90-305V~ 50/60Hz
Driver Protection	Mains surge 2Kv

Mechanical features	
Housing material	Aluminum frame
Housing color	White RAL 9010
IP	IP44 Front side
Diffuser / Protective shield	Opal polycarbonate
Mounting	Recessed
Hole dimension	 180
Cable	Cm.30
Operating ambient temperature	-20°C / +45°C
Storage ambient temperature	-20°C / +60°C
Item Dimensions	55mm Ø207mm - 0,7kg

Others	
Luminous Flux Maintenance	L80 50000h
Driver Lifespan	>50000
Packaging Dimensions	300x80x210mm - 1kg
International standard compliance	EN 60598-1; EN60598-2-2; EN62471 + IEC TR 62778; EN55015; EN61000-3-2; EN61000-3-3; EN 50581;
Eancode	8019282554622
Insulation Class	 CL2

CE

