
Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it





PSAR3-R 5W RED 115V DALI B.CO EMC EM1,5H

6823-10-302

Recessed fixture for living rooms

Lighting features	
LED Characteristics	**SMD**
Number of LEDs	**30**
Item Lumen	**61 lm**
Item Efficiency	**13 lm/W @85°C**
Color Temperature	**Red Dominant Wavelength: >619nm <625nm**
Optics	**Opal**
Minimum CRI	**80**
Photobiological Risk	**RG0**
Emergency Function	**Yes**
Emergency Lumen	**61**

Electrical features	
Input Voltage	**120/240V AC 50/60Hz**
Total Absorbed Power	**9W**
Power Factor	**> 0,9**
Control System	**DALI**
Driver	**Included**
Power Supply Type	**Costant Voltage**
Driver Output	**24V DC**
Driver Input	**108/264V AC 50/60Hz**

Mechanical features	
Housing material	**Aluminum frame and polycarbonate**
Housing color	**White RAL 9010**
IP	**IP44 Front side**
Cable gland, cable Ø min-max	**N°1 PG M20x1.5 EMC, Øext. cable: min 9mm - max 16mm; N°1 PG M16x1.5 for lamp**
Mounting	**Recessed**
Hole dimension	**260**
Cable	**1.0m Shielded cable (driver-lamp)**
Operating ambient temperature	**-20°C / +45°C**
Storage ambient temperature	**-20°C / +60°C**
Item Dimensions	**55mm Ø320mm - 1,3kg**

Others	
Luminous Flux Maintenance	**L80 50000h**
Driver Lifespan	**50000**
Packaging Dimensions	
International standard compliance	**EN 60598-1; EN60598-2-2; EN60598-2-22; EN62471 + IEC TR 62778; EN55015; EN61000-3-2; EN61000-3-3; EN 50581;**
Eancode	**8019282575290**
Insulation Class	**CL1**

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

