




PSAR 12W NW 6823-84-257

Recessed fixture for living rooms

Lighting features	
LED Characteristics	SMD
Number of LEDs	30
Light Source Lumen	1750 lm
Item Lumen	1250 lm
Light Source Efficiency	152 lm/W @85°C
Item Efficiency	97 lm/W @85°C
Color Temperature	White 4000K
Optics	Opal
Minimum CRI	80
SDCM	3 STEP
Photobiological Risk	RG0
Energy Efficiency Class	A A G D

Electrical features	
Input Voltage	220/240V 0-50/60Hz
Total Absorbed Power	12W
Power Factor	> 0,9
Control System	YES, Dimmable signal 0-10V
Driver	Included
Power Supply Type	Costant Current
Driver Output	700mA
Driver Input	220/240V 0-50/60Hz
Driver Protection	Mains surge 2Kv

Mechanical features	
Housing material	Aluminum frame
Housing color	White RAL 9010
IP	IP44 Front side
Diffuser / Protective shield	Opal acrylic
Mounting	Recessed
Hole dimension	 125
Cable	Cm.35 - H05RN-F 2x1
Operating ambient temperature	-20°C / +45°C
Storage ambient temperature	-20°C / +60°C
Item Dimensions	49mm Ø142mm - 0,7kg

Others	
Luminous Flux Maintenance	L80 50000h
Driver Lifespan	50000
Packaging Dimensions	150x100x150mm - 1kg
International standard compliance	EN 60598-1; EN 60598-2-2; EN 62471 + IEC TR 62778; EN 55015; EN 61547; EN 61000-3-2; EN 61000-3-3; EN IEC 63000;
Eancode	8019282560203
Insulation Class	 CL2



