




PSAR B 6823-89-259

Blue Light - Recessed fixture for living rooms

Lighting features	
LED Characteristics	SMD
Number of LEDs	6
Item Lumen	7 lm
Item Efficiency	4.5 lm/W @85°C
Color Temperature	Blue Dominant Wavelength: >465nm <471nm
Optics	Opal
Photobiological Risk	RG0

Electrical features	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	1W
Power Factor	> 0,9
Control System	On/Off
Driver	Included
Power Supply Type	Costant Voltage
Driver Output	24VDC
Driver Input	220/240V~ 50/60Hz
Driver Protection	Mains surge 1kV; (L/N - PE) 2kV

Mechanical features	
Housing material	Aluminum frame
Housing color	White RAL 9010
IP	IP44 Front side
Diffuser / Protective shield	Opal acrylic
Mounting	Recessed
Hole dimension	 125
Cable	Cm.35 - H05RN-F 2x1
Operating ambient temperature	-20°C / +45°C
Storage ambient temperature	-20°C / +60°C
Item Dimensions	49mm Ø142mm - 0,7kg

Others	
Luminous Flux Maintenance	L80 50000h
Driver Lifespan	100000
Packaging Dimensions	150x100x150mm - 1kg
International standard compliance	EN 60598-1; EN60598-2-2; EN62471 + IEC TR 62778; EN55015; EN61000-3-2; EN61000-3-3; EN 50581;
Eancode	8019282514275
Insulation Class	 CL2

CE

