
Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it





TVE-ST 33W NW -40°C JB-EMC

6868-54-073

Multipurpose white LED light fixture for inside and outside technical areas (-40°C). Housing white RAL9010

Lighting features	
LED Characteristics	**SMD**
Number of LEDs	**60**
Light Source Lumen	**3250 lm**
Item Lumen	**2645 lm**
Light Source Efficiency	**185 lm/W @85°C**
Item Efficiency	**80 lm/W @85°C**
Color Temperature	**White 4000K**
Optics	**180°**
Typical CRI	**85**
Minimum CRI	**80**
SDCM	**3 STEP**
Photobiological Risk	**RG0**
Energy Efficiency Class	A↑G C

Electrical features	
Input Voltage	**100/240V AC 50/60Hz**
Total Absorbed Power	**33W**
Power Factor	**> 0,9**
Control System	**On/Off**
Driver	**Included**
Power Supply Type	**Costant Current**
Driver Output	**1050mA**
Driver Input	**90/305V~ 50/60Hz**
Driver Protection	**Mains surge 4kV; (L/N - PE) 6KV**
Through-Wiring	**Yes, in the junction box**

Mechanical features	
Housing material	**Die-cast aluminum copper free EN AB 44100**
Surface treatment	**Polyester Painting**
Housing color	**White RAL 9010**
IP	**IP66**
IK	**10**
Diffuser / Protective shield	**Opal policarbonate flame rating V0 (UL94), UV resistent**
Cable gland, cable Ø min-max	**N°2 PG M20x1.5 EMC, Øext. cable: min 9mm - max 16mm**
Mounting	**With stainless steel brackets AISI 316L; fixing with M8 screws**
Corrosion category	**Salt Spray Resistance ASTM B117 >1500 hours**
Operating ambient temperature	**-40°C / +55°C**
Storage ambient temperature	**-40°C / +85°C**
Item Dimensions	**400x100x171mm - 3,45kg**

Others	
Luminous Flux Maintenance	**L80 100000h**
Driver Lifespan	**100000h**
Packaging Dimensions	**490x130x190mm - 3.7kg**
International standard compliance	**EN 60598-1; EN 60598-2-1; IEC 60092-306; IEC 60533 ; EN 62471 + IEC TR62778**
Eancode	**8019282580911**
Made In	**Italy**
Insulation Class	CL1

CE

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

