


**TVE-FL 22W NW RAL9010**


**6868-54-601**

Multipurpose white LED light fixture for inside and outside technical areas. Housing white RAL9010

| Lighting features       |   |
|-------------------------|---|
| LED Characteristics     | <b>SMD</b>  |
| Number of LEDs          | <b>60</b>   |
| Light Source Lumen      | <b>3250 lm</b>  |
| Item Lumen              | <b>2645 lm</b>  |
| Light Source Efficiency | <b>185 lm/W @ 85°C</b>  |
| Item Efficiency         | <b>120 lm/W @ 85°C</b>  |
| Color Temperature       | <b>White 4000K</b>  |
| Optics                  | <b>180°</b>   |
| Typical CRI             | <b>85</b>   |
| Minimum CRI             | <b>80</b>   |
| SDCM                    | <b>3 STEP</b>   |
| Photobiological Risk    | <b>RG0</b>  |
| Energy Efficiency Class |  |

| Mechanical features           |   |
|-------------------------------|---|
| Housing material              | <b>Die-cast aluminum copper free EN AB 44100</b>                      |
| Surface treatment             | <b>Polyester Painting</b>   |
| Housing color                 | <b>White RAL 9010</b>   |
| IP                            | <b>IP66 / IP67</b>  |
| IK                            | <b>10</b>   |
| Diffuser / Protective shield  | <b>Opal polycarbonate flame rating V0 (UL94), UV resistant</b>        |
| Cable gland, cable Ø min-max  | <b>N°2 PG M20x1.5, Øext. cable: min 6mm - max 12mm</b>                |
| Mounting                      | <b>With stainless steel brackets AISI 316L; fixing with M8 screws</b> |
| Corrosion category            | <b>Salt Spray Resistance ASTM B117 &gt;1500 hours</b>                 |
| Operating ambient temperature | <b>-25°C / +55°C</b>  |
| Storage ambient temperature   | <b>-25°C / +85°C</b>  |
| Item Dimensions               | <b>668x100x101mm - 3,2kg</b>  |

| Electrical features  |                                 |
|----------------------|---------------------------------|
| Input Voltage        | <b>100/240V AC 50/60Hz</b>      |
| Total Absorbed Power | <b>22W</b>                      |
| Power Factor         | <b>&gt; 0,9</b>                 |
| Control System       | <b>On/Off</b>                   |
| Driver               | <b>Included</b>                 |
| Power Supply Type    | <b>Costant Current</b>          |
| Driver Output        | <b>1050mA</b>                   |
| Driver Input         | <b>100/240V~ 50/60Hz</b>        |
| Driver Protection    | <b>Mains surge 1kV</b>          |
| Through-Wiring       | <b>Yes, in the junction box</b> |

| Others                            |   |
|-----------------------------------|---|
| Luminous Flux Maintenance         | <b>L80 100000h</b>  |
| Driver Lifespan                   | <b>100000h</b>  |
| Packaging Dimensions              | <b>3.5kg</b>  |
| International standard compliance | <b>EN 60598-1; EN 60598-2-1; IEC 60092-306; IEC 60533 ; EN 62471 + IEC TR62778; EN55015; EN 61547-1; EN61000-3-2; EN61000-3-3</b> |
| Eancode                           | <b>8019282573463</b>  |
| Made In                           | <b>Italy</b>  |
| Insulation Class                  | <br><b>CL1</b>                               |



