



## TGL 6869-54-501

Multipurpose lamp for technical rooms - High light power

Lighting features	
LED Characteristics	<b>SMD</b>
Number of LEDs	<b>120</b>
Light Source Lumen	<b>5400 lm</b>
Item Lumen	<b>4560 lm</b>
Light Source Efficiency	<b>180 lm/W @ 85°C</b>
Item Efficiency	<b>130 lm/W @ 85°C</b>
Color Temperature	<b>White 4000K</b>
Optics	<b>180°</b>
Typical CRI	<b>85</b>
Minimum CRI	<b>80</b>
SDCM	<b>3 STEP</b>
Photobiological Risk	<b>RG0</b>
Energy Efficiency Class	

Electrical features	
Input Voltage	<b>100/240V AC 50/60Hz</b>
Total Absorbed Power	<b>35W</b>
Power Factor	<b>&gt; 0,9</b>
Control System	<b>On/Off</b>
Driver	<b>Included</b>
Power Supply Type	<b>Constant Current</b>
Driver Output	<b>1750mA</b>
Driver Input	<b>100/240V~ 50/60Hz</b>
Driver Protection	<b>Mains surge 4kV; (L/N - PE) 6KV</b>
Through-Wiring	<b>Yes, in the junction box</b>

Mechanical features	
Housing material	<b>Die-cast aluminum copper free EN AB 44100</b>
Surface treatment	<b>Polyester Painting</b>
Housing color	<b>White RAL 9010</b>
IP	<b>IP66</b>
IK	<b>10</b>
MIL-S 9001D Grade A- Class I – Type A	<b>SI</b>
Diffuser / Protective shield	<b>Opal polycarbonate flame rating V0 (UL94), UV resistant</b>
Cable gland, cable Ø min-max	<b>N°2 PG M20x1.5, Øext. cable: min 6mm - max 12mm</b>
Mounting	<b>With stainless steel brackets AISI 316L; fixing with M8 screws</b>
Corrosion category	<b>Salt Spray Resistance ASTM B117 &gt;1500 hours</b>
Operating ambient temperature	<b>-40°C / +55°C</b>
Storage ambient temperature	<b>-40°C / +85°C</b>
Item Dimensions	<b>668x124x133mm - 3kg</b>

Others	
Luminous Flux Maintenance	<b>L80 100000h</b>
Driver Lifespan	<b>110000</b>
Packaging Dimensions	<b>3.5kg</b>
International standard compliance	<b>EN60598-1; EN60598-2-1; IEC60092-306; IEC60533; EN62471 + TR62778; EN55015; EN61547-1; EN61000-3-2; EN61000-3-3</b>
Eancode	<b>8019282556190</b>
Made In	<b>Italy</b>
Insulation Class	 <b>CL1</b>

CE

