
Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it





RTL 13W CCT

6879-10-954

Ceiling recessed LED. Suitable for indoor lighting, offices, reception and open space areas. Aluminum frame, color white.

Lighting features	
LED Characteristics	**SMD**
Number of LEDs	**24+24**
Light Source Lumen	**1359 lm**
Item Lumen	**1012 lm**
Light Source Efficiency	**130 lm/W @85°C**
Item Efficiency	**78 lm/W @85°C**
Color Temperature	**CCT (2700K 3000K 4000K)**
Optics	**Opal**
Minimum CRI	**90**
SDCM	**3 STEP**
Photobiological Risk	**RG0**
Energy Efficiency Class	A↑G E

Electrical features	
Input Voltage	**220/240V 0-50/60Hz**
Total Absorbed Power	**13W**
Power Factor	**> 0,7**
Control System	**On/Off**
Driver	**Included**
Power Supply Type	**Costant Current**
Driver Output	**300mA**
Driver Input	**220/240V 0-50/60Hz**
Driver Protection	**Mains surge 1kV; (L/N - PE) 2kV**

Mechanical features	
Housing material	**Aluminum frame and polycarbonate**
Housing color	**White RAL 9010**
IP	**IP54 Front side**
IK	**06**
Diffuser / Protective shield	**Opal policarbonate**
Mounting	**Recessed**
Hole dimension	**90 - 95**
Cable	**Cm.35 - H05RN-F 2x1**
Operating ambient temperature	**-20°C / +45°C**
Storage ambient temperature	**-20°C / +50°C**
Item Dimensions	**38mm Ø110mm - 0,25kg**

Others	
Luminous Flux Maintenance	**L80 50000h**
Driver Lifespan	**100000**
Packaging Dimensions	**115x90x115mm - 0.3kg**
International standard compliance	**EN 60598-1; EN60598-2-2; EN62471 + IEC TR 62778; EN55015; EN61000-3-2; EN61000-3-3; EN 50581;**
Eancode	**8019282570141**
Insulation Class	**CL2**

CE

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

