




## TON 100

# 6942-94-324

Powerful, precise and robust LED floodlight - Compact and low weight housing One lens for each LED assure intense and precise light beam

| Lighting features       |                       |
|-------------------------|-----------------------|
| LED Characteristics     | <b>Power LED</b>      |
| Number of LEDs          | <b>12</b>             |
| Light Source Lumen      | <b>12840 lm</b>       |
| Item Lumen              | <b>11383 lm</b>       |
| Light Source Efficiency | <b>135 lm/W @85°C</b> |
| Item Efficiency         | <b>108 lm/W @85°C</b> |
| Color Temperature       | <b>White 4000K</b>    |
| Optics                  | <b>26°</b>            |
| Minimum CRI             | <b>80</b>             |
| SDCM                    | <b>3 STEP</b>         |
| Photobiological Risk    | <b>RG1</b>            |
| Energy Efficiency Class | <b>A</b><br><b>E</b>  |

| Electrical features  |                                         |
|----------------------|-----------------------------------------|
| Input Voltage        | <b>100/240V AC 50/60Hz</b>              |
| Total Absorbed Power | <b>105W</b>                             |
| Power Factor         | <b>&gt; 0,95</b>                        |
| Driver               | <b>Included</b>                         |
| Power Supply Type    | <b>Costant Current</b>                  |
| Driver Output        | <b>700mA</b>                            |
| Driver Input         | <b>100/240V~ 50/60Hz</b>                |
| Driver Protection    | <b>Mains surge 6kV; (L/N - PE) 10kV</b> |

| Mechanical features                   |                                                                         |
|---------------------------------------|-------------------------------------------------------------------------|
| Housing material                      | <b>Die-cast aluminum copper free EN AB 44100</b>                        |
| Surface treatment                     | <b>Polyester Painting</b>                                               |
| Housing color                         | <b>Grey RAL 7040</b>                                                    |
| IP                                    | <b>IP66 / IP67</b>                                                      |
| IK                                    | <b>07</b>                                                               |
| MIL-S 9001D Grade A- Class I – Type A | <b>SI</b>                                                               |
| Diffuser / Protective shield          | <b>Extra-clear tempered glass, 4mm thick</b>                            |
| Cable gland, cable Ø min-max          | <b>M20x1.5 polyamide - Ø cable: min. 7mm - max. 12mm</b>                |
| Mounting                              | <b>With stainless steel bracket AISI 316L; fixing with 2 M12 screws</b> |
| Corrosion category                    | <b>Salt Spray Resistance ASTM B117 &gt;1500 hours</b>                   |
| Operating ambient temperature         | <b>-40°C / +55°C</b>                                                    |
| Storage ambient temperature           | <b>-40°C / +80°C</b>                                                    |
| Item Dimensions                       | <b>370x142x319mm - 8,5kg</b>                                            |

| Others                            |                                                                                             |
|-----------------------------------|---------------------------------------------------------------------------------------------|
| Luminous Flux Maintenance         | <b>L80 100000h</b>                                                                          |
| Driver Lifespan                   | <b>100000h</b>                                                                              |
| Packaging Dimensions              | <b>470x180x470mm - 9.5kg</b>                                                                |
| International standard compliance | <b>EN 60598-1; EN 60598-2-5; EN62471 + IEC TR 62778; EN 50581; IEC 60533; IEC 60092-306</b> |
| Eancode                           | <b>8019282538882</b>                                                                        |
| Made In                           | <b>Italy</b>                                                                                |
| Insulation Class                  | <b>CL1</b>                                                                                  |

CE

