



## Alim2 6951-00-002

| Electrical features  |                            |
|----------------------|----------------------------|
| Input Voltage        | <b>100/240V AC 50/60Hz</b> |
| Total Absorbed Power | <b>80W</b>                 |
| Power Factor         | <b>&gt; 0,9</b>            |
| Control System       | <b>On/Off</b>              |
| Power Supply Type    | <b>Costant Voltage</b>     |
| Driver Output        | <b>24VDC</b>               |
| Driver Input         | <b>90/305V~ 50/60Hz</b>    |
| Driver Protection    | <b>Mains surge 2Kv</b>     |

| Mechanical features          |                                                                                    |
|------------------------------|------------------------------------------------------------------------------------|
| Housing material             | <b>Metal frame</b>                                                                 |
| Surface treatment            | <b>Painting</b>                                                                    |
| Housing color                | <b>White RAL 9010</b>                                                              |
| IP                           | <b>IP55</b>                                                                        |
| Cable gland, cable Ø min-max | <b>Cable entry M20 cable gland: Ø6-12mm;<br/>Cable exit on connector: Ø7-9.5mm</b> |
| Item Dimensions              | <b>550x97x300mm - 3,2kg</b>                                                        |

| Others                            |                                                                                                |
|-----------------------------------|------------------------------------------------------------------------------------------------|
| Driver Lifespan                   | <b>50000</b>                                                                                   |
| Packaging Dimensions              | <b>3.4kg</b>                                                                                   |
| International standard compliance | <b>EN 55015; EN 61000-3-2; EN 61000-3-3; EN 61347-1; EN 61347-2-13; EN 61547; EN IEC 63000</b> |
| Eancode                           | <b>8019282514909</b>                                                                           |
| Insulation Class                  | <b>CL1</b>                                                                                     |

