


**GLO-B**
**6952-96-003**

LED Globe – BLUE light – Cable glands not included, refer to accessories EX LED Globe – BLUE light – ONLY with EX Cable glands not included, refer to accessories Shock proof MIL S 901 D certified Grade A - Class I - Type A - only if mounted with our wall or ceiling brackets accessories. Protection guard available, refer to our accessories. Installation hazardous areas: Zone 1/2 (Gases) - Zone 21/22 (Dusts) Classifications GROUP II - Category 2G/2D II 2G Ex db IIC T4 Gb - II 2D Ex tb IIIC T135°C Db

Lighting features		Mechanical features	
LED Characteristics	<b>Power LED</b>	Housing material	<b>Marine grade copper free aluminium</b>
Number of LEDs	<b>1</b>	Surface treatment	<b>External epoxy powders</b>
Color Temperature	<b>Blue Dominant Wavelength: &gt;440nm &lt;460nm</b>	Housing color	<b>Grey RAL 7040</b>
Optics	<b>180°</b>	IP	<b>IP66</b>
Photobiological Risk	<b>RG0</b>	MIL-S 9001D Grade A- Class I – Type A	<b>SI</b>
Electrical features		Others	
Input Voltage	<b>100/240V AC 50/60Hz</b>	Driver Lifespan	<b>90000</b>
Total Absorbed Power	<b>7W</b>	Packaging Dimensions	<b>180x300x180mm - 4kg</b>
Power Factor	<b>&gt; 0,9</b>	International standard compliance	<b>EN60598-1; EN60598-2-1; EN62471 + TR62778; IEC60092-306; IEC60533; EN60079-0; EN 60079-1; EN60079-28; EN 60079-31</b>
Control System	<b>On/Off</b>	Eancode	<b>8019282550433</b>
Driver	<b>Included</b>	Made In	<b>Italy</b>
Power Supply Type	<b>Costant Current</b>	Insulation Class	
Driver Output	<b>500mA</b>		
Driver Input	<b>100/240V~ 50/60Hz</b>		
Driver Protection	<b>Mains surge 1kV</b>		
Through-Wiring	<b>Yes, in the lamp</b>		



