


GLO-O
6952-96-004

LED Globe – ORANGE light – Cable glands not included, refer to accessories EX LED Globe – ORANGE light – ONLY with EX Cable glands not included, refer to accessories Shock proof MIL S 901 D certified Grade A - Class I - Type A - only if mounted with our wall or ceiling brackets accessories. Protection guard available, refer to our accessories. Installation hazardous areas: Zone 1/2 (Gases) - Zone 21/22 (Dusts) Classifications GROUP II - Category 2G/2D II 2G Ex db IIC T4 Gb - II 2D Ex tb IIIC T135°C Db

Lighting features		Mechanical features	
LED Characteristics	Power LED	Housing material	Marine grade copper free aluminium
Number of LEDs	1	Surface treatment	External epoxy powders
Color Temperature	Orange Dominant Wavelength: >588nm <592nm	Housing color	Grey RAL 7040
Optics	180°	IP	IP66
Photobiological Risk	RG0	MIL-S 9001D Grade A- Class I – Type A	SI

Electrical features		Others	
Input Voltage	100/240V AC 50/60Hz	Driver Lifespan	90000
Total Absorbed Power	7W	Packaging Dimensions	180x300x180mm - 4kg
Power Factor	> 0,9	International standard compliance	EN60598-1; EN60598-2-1; EN62471 + TR62778; IEC60092-306; IEC60533; EN60079-0; EN 60079-1; EN60079-28; EN 60079-31
Control System	On/Off	Eancode	8019282550440
Driver	Included	Made In	Italy
Power Supply Type	Costant Current	Insulation Class	 CL1
Driver Output	500mA		
Driver Input	100/240V~ 50/60Hz		
Driver Protection	Mains surge 1kV		
Through-Wiring	Yes, in the lamp		



