



STARFIX 20-630 120V NW 9016 PC OPALE 6955-54-007

21,5 W LED fixture – length 630 mm

Lighting features	
LED Characteristics	SMD
Number of LEDs	140
Light Source Lumen	3065 lm
Item Lumen	2624 lm
Light Source Efficiency	163 lm/W @ 85°C
Item Efficiency	122 lm/W @ 85°C
Color Temperature	White 4000K
Optics	180°
Typical CRI	92
Minimum CRI	90
SDCM	3 STEP
Photobiological Risk	RG0
Energy Efficiency Class	

Electrical features	
Input Voltage	120/277V AC 50/60Hz
Total Absorbed Power	21,5W
Power Factor	>0,95
Control System	On/Off
Driver	Included
Power Supply Type	Constant Current
Driver Output	500mA
Driver Input	108/305V AC 50/60Hz
Driver Protection	Mains surge 2Kv
Through-Wiring	Yes, in the lamp

Mechanical features	
Housing material	Pre-hot dip galvanized steel, thickness 7/10
Surface treatment	Polyester Painting
Housing color	White RAL 9016
IP	IP66 / IP67
IK	10
Diffuser / Protective shield	Opal polycarbonate flame rating V0 (UL94), UV resistant
Cable gland, cable Ø min-max	N°2 M20 nickel plated brass - Cable Ø 8-15mm + N°1 M20 cap
Clips	N°6, Stainless steel AISI 316SS
Mounting	M8 treaded pin with nut on preinstalled bushing, all stainless steel AISI 316L
Operating ambient temperature	-25°C / +55°C
Storage ambient temperature	-25°C / +70°C
Item Dimensions	L629xP133xH82mm - 2,4kg

Others	
Luminous Flux Maintenance	L80 B10 >75.000
Driver Lifespan	100.000 h with failure rate less than 10%
Packaging Dimensions	680x170x110mm - 2.7kg
International standard compliance	EN 60598-1; EN 60598-2-1; Lloyd's Register: 2020 + Notice 2021; EN 62471 + TR62778; EN IEC 63000:2018
Eancode	8019282558705
Made In	Italy
Insulation Class	 CL1



