



STARFIX 20-630 INOX

6955-54-108

20W 24VDC outdoor open deck LED fixture. Stainless steel AISI 316L housing – length 630 mm

Lighting features	
LED Characteristics	SMD
Number of LEDs	140
Light Source Lumen	3065 lm
Item Lumen	2624 lm
Light Source Efficiency	163 lm/W @85°C
Item Efficiency	125 lm/W @85°C
Color Temperature	White 4000K
Optics	180°
Typical CRI	92
Minimum CRI	90
SDCM	3 STEP
Photobiological Risk	RG0
Energy Efficiency Class	A++ D

Electrical features	
Input Voltage	18/32V DC
Total Absorbed Power	20W
Power Factor	1
Control System	On/Off
Driver	Included
Power Supply Type	Constant Current
Driver Output	500mA
Driver Input	18-32VDC
Driver Protection	Over Voltage max 80V DC
Through-Wiring	Yes, in the lamp

Mechanical features	
Housing material	Stainless steel AISI 316L
Surface treatment	Polyester Painting
Housing color	White RAL 9016
IP	IP66 / IP67
IK	10
Diffuser / Protective shield	Opal polycarbonate flame rating V0 (UL94), UV resistant
Cable gland, cable Ø min-max	M20 nickel plated brass - Cable Ø 8-15mm
Clips	Yes, Stainless steel AISI 316SS
Mounting	M8 treaded pin with nut on preinstalled bushing, all stainless steel AISI 316L
Operating ambient temperature	-25°C / +55°C
Storage ambient temperature	-25°C / +70°C
Item Dimensions	629x82x133mm - 2,4kg

Others	
Luminous Flux Maintenance	L80 B10 >75.000
Driver Lifespan	>35.000h
Packaging Dimensions	2.7kg
International standard compliance	EN 60598-1; EN 60598-2-1; EN 62471 + TR 62778; EN 50581; EN 55015; EN 61547
Eancode	8019282561514
Made In	Italy
Insulation Class	III CL3



