




STARFIX 40-1190 EM 3H

6955-54-113

40 W LED fixture – length 1190 mm - EMERGENCY 3h - INOX

Lighting features	
LED Characteristics	SMD
Number of LEDs	280
Light Source Lumen	6130 lm
Item Lumen	4626 lm
Light Source Efficiency	162 lm/W @85°C
Item Efficiency	112 lm/W @85°C
Color Temperature	White 4000K
Optics	180°
Typical CRI	92
Minimum CRI	90
SDCM	3 STEP
Photobiological Risk	RG0
Emergency Function	YES - 3h autonomy
Emergency Lumen	15%
Energy Efficiency Class	A ↑ D

Electrical features	
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	41W
Power Factor	>0,95
Control System	On/Off
Driver	Included
Power Supply Type	Costant Current
Driver Output	1000mA
Driver Input	198-264VAC 50/60Hz
Driver Protection	Mains surge 1kV; (L/N - PE) 2kV
Through-Wiring	Yes, in the lamp

Mechanical features	
Housing material	Stainless steel AISI 316L
Surface treatment	Polyester Painting
Housing color	White RAL 9016
IP	IP66 / IP67
IK	10
Diffuser / Protective shield	Opal polycarbonate flame rating V0 (UL94), UV resistant
Cable gland, cable Ø min-max	M20 nickel plated brass - Cable Ø 8-15mm
Clips	Yes, Stainless steel AISI 316SS
Mounting	M8 treaded pin with nut on preinstalled bushing, all stainless steel AISI 316L
Operating ambient temperature	-0°C / +45°C
Storage ambient temperature	-20°C / +35°C 15 months
Item Dimensions	1189x82x133mm - 4.6kg

Others	
Luminous Flux Maintenance	L80 B10 >75.000 h
Driver Lifespan	100.000 h with failure rate less than 10%
Packaging Dimensions	1200x100x155mm - 5.2kg
International standard compliance	EN 60598-1; EN 60598-2-1; EN 62471 + TR62778; EN IEC 63000:2018
Eancode	8019282568629
Made In	Italy
Insulation Class	CL1



