


STARFIX 20-630 120V NW 9016 PC INOX EMC


6955-54-116

20 W outdoor open deck LED fixture. Stainless steel AISI 316L housing – length 630 mm - EMC cable gland -

Lighting features	
LED Characteristics	SMD
Number of LEDs	140
Light Source Lumen	3065 lm
Item Lumen	2624 lm
Light Source Efficiency	163 lm/W @ 85°C
Item Efficiency	122 lm/W @ 85°C
Color Temperature	White 4000K
Optics	180°
Typical CRI	92
Minimum CRI	90
SDCM	3 STEP
Photobiological Risk	RG0
Energy Efficiency Class	

Electrical features	
Input Voltage	120/277V AC 50/60Hz
Total Absorbed Power	21,5W
Power Factor	>0,98
Control System	On/Off
Driver	Included
Power Supply Type	Costant Current
Driver Output	500mA
Driver Input	108-305V AC 50/60Hz
Driver Protection	Mains surge 2Kv
Through-Wiring	Yes, in the lamp

Mechanical features	
Housing material	Stainless steel AISI 316L
Surface treatment	Polyester Painting
Housing color	White RAL 9016
IP	IP66 / IP67
IK	10
Diffuser / Protective shield	Opal polycarbonate flame rating V0 (UL94), UV resistant
Cable gland, cable Ø min-max	N°2 PG M20x1.5 EMC nickel plated brass, Øext. cable: min 9mm - max 16mm
Clips	Yes, Stainless steel AISI 316SS
Mounting	M8 threaded pin with nut on preinstalled bushing, all stainless steel AISI 316L
Operating ambient temperature	-25°C / +55°C
Storage ambient temperature	-25°C / +70°C
Item Dimensions	629x82x133mm - 2,4kg

Others	
Luminous Flux Maintenance	L80 B10 >75.000
Driver Lifespan	100.000 h with failure rate less than 10%
Packaging Dimensions	690x110x170mm - 2.7kg
International standard compliance	EN 60598-1; EN 60598-2-1; EN 62471 + TR62778; EN IEC 63000:2018
Eancode	8019282575627
Made In	Italy
Insulation Class	 CL1



