




STARFIX 20-630 INOX EM.1h

6955-54-121

20 W outdoor open deck LED fixture. Stainless steel AISI 316L housing – length 630 mm - emergency 1h

Lighting features	
LED Characteristics	SMD
Number of LEDs	140
Light Source Lumen	3065 lm
Item Lumen	2624 lm
Light Source Efficiency	163 lm/W @85°C
Item Efficiency	122 lm/W @85°C
Color Temperature	White 4000K
Optics	180°
Typical CRI	92
Minimum CRI	90
SDCM	3 STEP
Photobiological Risk	RG0
Emergency Function	YES - 1h autonomy
Emergency Lumen	30%
Energy Efficiency Class	A D

Electrical features	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	21,5W
Power Factor	>0,95
Control System	On/Off
Driver	Included
Power Supply Type	Costant Current
Driver Output	500mA
Driver Input	198-264VAC 50/60Hz
Driver Protection	Mains surge 1kV; (L/N - PE) 2kV
Through-Wiring	Yes, in the lamp

Mechanical features	
Housing material	Stainless steel AISI 316L, thickness 7/10
Surface treatment	Polyester Painting
Housing color	White RAL 9016
IP	IP67
IK	10
Diffuser / Protective shield	Opal polycarbonate flame rating V0 (UL94), UV resistant
Cable gland, cable Ø min-max	M20 nickel plated brass - Cable Ø 8-15mm
Clips	Yes, Stainless steel AISI 316SS
Mounting	M8 threaded pin with nut on preinstalled bushing, all stainless steel AISI 316L
Operating ambient temperature	0°C / +45°C
Storage ambient temperature	-20°C / +35°C 15 months
Item Dimensions	629x82x133mm - 3kg

Others	
Luminous Flux Maintenance	L80 B10 >75.000
Driver Lifespan	100.000 h with failure rate less than 10%
Packaging Dimensions	645x120x190mm - 3.4kg
International standard compliance	EN 60598-1; EN60598-2-1; EN62471 + IEC TR 62778; EN55015; EN61000-3-2; EN61000-3-3; EN IEC 63000:2018
Eancode	8019282579557
Made In	Italy
Insulation Class	CL1

CE

