

STARFIX 20-630 INOX - BK 6955-55-201

23W outdoor open deck LED fixture, 2 stainless steel brackets 45° for bulkhead fixing included Stainless steel AISI 316L housing – length 630 mm





Lighting features	
LED Characteristics	SMD
Number of LEDs	140
Light Source Lumen	2890 lm
Item Lumen	2470 lm
Light Source Efficiency	141 lm/W @ 85°C
Item Efficiency	107 lm/W @ 85°C
Color Temperature	White 6500K
Optics	180°
Typical CRI	92
Minimum CRI	90
SDCM	3 STEP
Photobiological Risk	RG0
Energy Efficiency Class	

Electrical features	
Input Voltage	220/240V 0-50/60Hz
Total Absorbed Power	23W
Power Factor	>0,95
Control System	On/Off
Driver	Included
Power Supply Type	Costant Current
Driver Output	500mA
Driver Input	198-264VAC 50/60Hz / 176-280VDC
Driver Protection	Mains surge 1kV; (L/N - PE) 2kV
Through-Wiring	Yes, in the lamp

Mechanical features	
Housing material	Stainless steel AISI 316L, thickness 7/10
Surface treatment	Polyester Painting
Housing color	White RAL 9016
IP	IP66 / IP67
IK	10
Diffuser / Protective shield	Opal polycarbonate flame rating V0 (UL94), UV resistant
Clips	N°6 Stainless steel AISI 316SS
Mounting	With pair of 135° bent supports with M30 fixing
Operating ambient temperature	-25°C / +55°C
Storage ambient temperature	-25°C / +70°C
Item Dimensions	L629xP133xH82mm - 3.8kg

Others	
Luminous Flux Maintenance	L80 B10 >75.000
Driver Lifespan	100.000 h with failure rate less than 10%
Packaging Dimensions	680x170x110mm - 4.1kg
International standard compliance	EN 60598-1; EN 60598-2-1; Lloyd's Register: 2020 + Notice 2021; EN 62471 + TR62778; EN IEC 63000:2018
Eancode	8019282572695
Made In	Italy
Insulation Class	 CL1





Circuit Breakers

Number of lamps that can be connected in parallel under a 10A C curve circuit breaker: n°35

